

RedKite-l

POWERFUL WIDE-AREA MOTION IMAGERY FOR THE INSITU INTEGRATOR™



3,000 ft - 12,000 ft (1,000 - 4,000 m) AGL

0.13 m at 3,000 ft (1,000 m) AGL

0.5 m at 12,000 ft (4,000 m) AGL

Control centers, mobile devices

1 km diameter from 3,000 ft (1,000 m) AGL

4 km diameter from 12,000 ft (4,000 m) AGL

Up to 10 unique streaming video windows

Compact embedded processing includes north-up rendering,

real-time and DVR-like streaming, and full-mission storage

Internal datalink, providing a fully integrated single LRU

PERFORMANCE

- Operational Altitude:
- Areas of Coverage:
- GSDs:
- Camera:
- Refresh Rate:
- Cross-cueing:
- Viewer Windows:
- Onboard Archive Length: > 4 hrs, expandable to 8 hrs
- GCS/SCS Archive Length: 100 hrs, expandable
- Imagery Transmission: Internal Processing:

Datalink:

PAYLOAD SIZE, WEIGHT, AND POWER

- Bay Size:
- Bay Weight:
- Bay Power:
- Processing:
- < 300 W (peak)
- Processing embedded in payload

GROUND/SENSOR CONTROL STATION (GCS/SCS) SIZE, WEIGHT, AND POWER

- Sensor Control and Exploitation:
- Components: GCS/SCS Size:

• GCS/SCS Weight:

• GCS/SCS Power:

- Client, archive server, storage array, acessories
- < 250 lbs (115 kg) / Up to 500 lbs (227 kg) with cases
- < 1 KW, 100% duty cycle

OPTIONAL SUPPORT

• Operations Support:

Full-time operation, maintenance, and repair at deployed sites Training, warranty support and 24/7 helpdesk support available

Ground-based (transportable or fixed) and/or aircraft-based

Integrator™ is a product of Insitu Inc.

Adapted to the payload bay of the Insitu Integrator, RedKite-I combines the power of widearea motion imagery (WAMI) with the flexibility of a small Group 3 UAS. RedKite-I transmits on demand, both real-time and forensic imagery to multiple users on the ground thanks to the system's unparalleled onboard processor.

- DEFENSE
- LAW ENFORCEMENT
- BORDER SECURITY

Logos Technologies LLC An Elbit Systems of America Company

2701 Prosperity Avenue, Suite 400 Fairfax, Virginia 22031 +1.703.584.5725

RK-I.46012302.SK

- 9 U, 30 in rack depth

41 in L x 12 in W x 8 in H (105 cm x 31 cm x 21 cm) < 25 lbs (11 kg)

> 50 Mpx

≥2Hz

Yes